



Coupler

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Removable centre stop up to d160

| d (mm) | Code | GP | Weight (kg) | d1 (mm) | L (mm) |
|-----------|--------------------|----|----------------|------------|-----------|
| 75 | 753 911 612 | 12 | 0.282 | 96 | 110 |
| 90 | 753 911 613 | 10 | 0.406 | 113 | 125 |
| 110 | 753 911 614 | 5 | 0.692 | 138 | 145 |
| 125 | 753 911 615 | 5 | 0.718 | 154 | 156 |
| 140 | 753 911 616 | 5 | 0.945 | 172 | 166 |
| 160 | 753 911 617 | 6 | 1.362 | 196 | 180 |
| 180 | 753 911 618 | 5 | 1.747 | 219 | 192 |
| 200 | 753 911 619 | 4 | 1.866 | 244 | 208 |
| 225 | 753 911 620 | 3 | 3.329 | 273 | 225 |
| 250 | 753 911 621 | 2 | 4.678 | 304 | 248 |
| 280 | 753 911 622 | 2 | 7.500 | 340 | 252 |
| 315 | 753 911 623 | 2 | 8.142 | 382 | 267 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: <http://www.gfps.com>