



L = length / Länge

Electrofusion saddle

- PE 100 SDR 11 (ISO S5)
 - 10 bar Gas / 16 bar Water
 - Complete with lower part
 - 4 mm pin connectors
 - Limited path fusion indicators
 - * Complete with moulded-on lower part
 - **Delivery without lower part for assembling as Top Load with tool no. 799.350.477
- Not suitable for all tapping-tees, tapping-valves and spigots with cutter of the modular systems;
SDR compatibility according to individual parts

	d (mm)	d1 (mm)	Code	SP	Weight (kg)	L (mm)
	63	63	193 131 037	1	0.325	165
	75	63	193 131 047	1	0.455	165
	90	63	193 131 057	1	0.415	165
	110	63	193 131 067	1	0.458	165
*	110	63	193 133 067	1	0.490	182
	125	63	193 131 077	1	0.502	165
	140	63	193 131 087	1	0.523	165
	160	63	193 131 097	1	0.493	165
*	160	63	193 133 097	1	0.543	182
	180	63	193 131 107	1	0.600	165
	200	63	193 131 117	1	0.634	165
	225	63	193 131 127	1	0.618	165
	250	63	193 131 137	1	0.627	165
**	280	63	193 131 147	1	0.359	165
**	315 - 355	63	193 131 157	1	0.373	165
**	400	63	193 131 177	1	0.356	165

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>