



WR 200 / WR 200 S

Welding Recorder for manually operated butt fusion machines (ECOS, TOP, GF, KL)

The WR 200 / WR 200 S assists the welder to ensure the quality of the butt-fusion jointing according to country specific standards. The user is guided through all preparation and fusion steps. The selection of the fusion data like the used material, welding standard, diameter and wall thickness (SDR) is supported by a menu. The complete fusion sequence is supervised and recorded. The welding protocols can be easily exported via USB stick to any personal computer for further management or printout. The welding protocols can be directly printed out at jobsite by means of the on-board printer (WR 200 only). The recorder is protected by a robust plastic case of IP 65 protection class. The power and connecting cables are stored in a separate box (WR 200) or in a compartment directly integrated in the case (WR 200 S). The WR 200 can be connected to hydraulically operated butt-fusion machines for construction site, even by later retrofitting of machines in service centres. The WR 200 S **ECO version** is also available, to specifically work in combination with ECO S machine models.

Description:

- Intuitive user guidance menu
- Welding standard selection e.g. DVS, UNI, WIS, ISO
- Welding process customisable: 4 user-defined cycles available
- Additional data input as: operator-ID, job and order number, joint number, GPS coordinates from an independent device
- On-board printer for direct print out of welding protocols at jobsite (WR 200 only)
- USB interface for welding protocols transfer
- Internal memory capacity: 250 protocols
- Selection of operator language
- Battery support for an autonomy of 10 hours (no data loss during power interruption)
- "Rent Guardian" function to set and control the rental period of the unit
- Available protocols format: TXT for easy printout, CSV for database management with Welding Book application
- Fully compatible with butt-fusion machines already working with former welding recorder models SUVI® 50 and WR 100
- Working temperature range: -10°C to +50°C

	Type Performance	Dimensions	Code	Weight (kg)
WR 200 S - ECO	230 V	350x300x250 mm	790 119 452	5.000
WR 200 S	230 V	350x300x250 mm	790 119 451	5.000
WR 200	230 V	350x300x250 mm	790 119 401	5.000
WR 200 S - ECO CYRILLIC	230 V	350x300x250 mm	790 119 455	5.000
WR 200 S CYRILLIC	230 V	350x300x250 mm	790 119 454	5.000
WR 200 CYRILLIC	230 V	350x300x250 mm	790 119 425	5.500

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>